



USB 2.0 to 4 Port RS-232 Serial Adapter Optical isolated



USB to RS232 Serial Adapter

Model No. USB2-4COM-SI-M



USB 2.0 Serial Adapter with Optical isolation and surge protection is available on each serial port and is individually optically isolated with 2000 volt DC optical isolation on 8 signal pins. Meets the highest level of optical isolation protecting your computer from spikes and surges.

- Incorporates Optical Isolation and Surge Protection over each port.
- Connects to a Host USB system port or USB Hub via USB cable
- Provides high speed serial port baud rate at 921.6Kbps
- Installed as a standard Windows COM port to communicate with Factory Automation, Bar Code Scanners, Time Clocks or other.

Interested? LEARN MORE →



[View more
images here >](#)

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ **1-727-209-1300** (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Environmental	Operating Temperature	0C to 55C
Performance	Isolated/Surge Protected	Yes
Hardware	Chipset	FTDI
Software	OS Support	Linux, Win 10, Win 7, Win 8, Win Vista, Win XP
Serial Attributes	Serial Standards	RS232
USB	Isolated/Surge Protected	Yes
	Screw Lock Compatible	Yes
	Color	White
Mechanical	Mounting Style	Din-Rail (Optional Bracket)
	Ports	4 Serial Ports
	Country of Origin	Taiwan
Compliance	Certifications	CE , FCC
	Compliance	TAA
	Connector	DB9 Male w/ Nuts
Other Data	Chip Model	FT4232HL, ZT213LFEA
	Weight	3.0 lbs

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

☎ **[1-888-688-2188](tel:1-888-688-2188)** (Toll free)

✉ **sales@coolgear.com**