



4 Port USB 3.2 Gen 1 Hub w/ Screw-Locking Ports & Status LEDs



Industrial Grade | +7~24V DC Input | Surface Mountable | 5 Gbps | LED Indicators

Model No. USBG-3X4M



- **Super Fast Speeds:** This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- **Superior Build Quality:** Housed in a rugged steel chassis with built in mountable flanges, the 4-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- **Check Your Ports' Status:** Quickly check the status of each port individually with built in LED indicators.
- **Upstream:** 1 USB port, Type B connector, Screw-lock type
- **Downstream:** 4 USB ports, Type A connectors, Screw-lock type
- **Power Connector:** 2-Pin Terminal Block, DC Barrel 2.1mm ID x 5.5mm OD
- **Mounting Options:** Wall & Surface
- **Supply Current:** 900mA USB Bus Power for Each Downstream Port

Interested? [LEARN MORE](#) →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Power	Input Voltage	+7~24V DC
	Power Source	2-Pin Terminal Block, AC Adapter Included, DC Barrel Jack 2.1mm ID x 5.5mm OD
	Idle Consumption	17.27 mA @ 12V Terminal Power, 38mA Bus Powered
	Adapter Input Current	1A
	Adapter Input Voltage	100~240V AC
	Adapter Output Current	3A
	Adapter Output Voltage	12V DC
	External Power Required	No
Compliance	Charging Protocols	Charging Downstream Port (CDP), Dedicated Charging Port (DCP)
	Per USB Port Current	900mA maximum
	Certifications	TAA Hubs , RoHS
	Color	Black
Physical Characteristics	Item Dimensions (L x W x H)	7.02 x 2.34 x 0.91 in.
	Item Weight	0.650 lbs.
	Mounting Style	Surface / Wall Mount
	Ports	4 USB Ports
	Material of Construction	Galvanized Steel
What's in the Box	Screw Lock Compatible	Yes
	Package Contents	2-Pin Terminal Block, Hub, Power Adapter, USB-A to USB-B Cable
	OS Support	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
Environmental	Operating Temperature	0°C to 55°C (32°F to 131°F)
	Storage Temperature	-20°C to 85°C (-4°F to 185°F)
	Humidity	5% ~ 95% (non-condensing)
Product Information	Warranty	1 year from date of purchase
	Chipset	VL811-Q8P
Hardware	Charging Protocols	Charging Downstream Port (CDP), Dedicated Charging Port (DCP)
	LED Indicators	Port Status, Power
	Downstream USB Ports	4 Type-A Female USB
	Upstream USB Ports	1 Type-B Female USB
Performance & Safety	Max Data Transfer Rate	5Gbps
	USB Interface	USB 3.2 Gen 1
	UPC	045079162303
Other Data	Series	WKS-UH (Workstation Series Hubs)
	Weight	1.85 lbs
	Dimensions	11.25 x 6.25 x 2 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

📞 **1-888-688-2188 (Toll free)**

✉ **sales@coolgear.com**