



4 Port USB 3.2 Gen 1 Hub w/ Screw-Locking Ports & Status LEDs



Industrial Grade | +7~24V DC Input | Surface Mountable | 5 Gbps | LED Indicators

Model No. USBG-3X4M



- **Super Fast Speeds:** This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- **Superior Build Quality:** Housed in a rugged steel chassis with built in mountable flanges, the 4-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- **Check Your Ports' Status:** Quickly check the status of each port individually with built in LED indicators.
- **Upstream:** 1 USB port, Type B connector, Screw-lock type
- **Downstream:** 4 USB ports, Type A connectors, Screw-lock type
- **Power Connector:** 2-Pin Terminal Block, DC Barrel 2.1mm ID x 5.5mm OD
- **Mounting Options:** Wall & Surface
- **Supply Current:** 900mA USB Bus Power for Each Downstream Port

Interested? [LEARN MORE](#) →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Environmental	Operating Temperature	0°C to 55°C (32°F to 131°F)
	Storage Temperature	-20°C to 85°C (-4°F to 185°F)
	Humidity	5% ~ 95% (non-condensing)
Performance	Max Data Transfer Rate	5Gbps
Hardware	Chipset	VL811-Q8P
	Charging Protocols	Charging Downstream Port (CDP), Dedicated Charging Port (DCP)
	LED Indicators	Port Status, Power
	Per USB Port Current	900mA maximum
Product Information	Warranty	1 year from date of purchase
Power	Input Voltage	+7~24V DC
	Power Source	2-Pin Terminal Block, AC Adapter Included, DC Barrel Jack 2.1mm ID x 5.5mm OD
	Idle Consumption	17.27 mA @ 12V Terminal Power, 38mA Bus Powered
	Adapter Input Current	1A
	Adapter Input Voltage	100~240V AC
	Adapter Output Current	3A
	Adapter Output Voltage	12V DC
	External Power Required	No
Software	OS Support	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
What's in the Box	Package Contents	2-Pin Terminal Block, Hub, Power Adapter, USB-A to USB-B Cable
USB	USB Type	USB 3.2 Gen 1
	Upstream USB Ports	1 Type-B Female USB
	Downstream USB Ports	4 Type-A Female USB
	Screw Lock Compatible	Yes
	Color	Black
Mechanical	Item Dimensions (L × W × H)	7.02 × 2.34 × 0.91 in.
	Item Weight	0.650 lbs.
	Mounting Style	Surface / Wall Mount
	Ports	4 USB Ports
	Material of Construction	Galvanized Steel
Compliance	Certifications	TAA Hubs , RoHS
Other Data	UPC	045079162303
	Series	WKS-UH (Workstation Series Hubs)
	Weight	1.85 lbs
	Dimensions	11.25 × 6.25 × 2 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

 **1-888-688-2188 (Toll free)**

 **sales@coolgear.com**