

4 Port USB 3.2 Gen 1 Powered Hub w/ ESD Surge Protection



Industrial Grade | +7~48V DC Input | Surface Mountable | DIN Rail | 5 Gbps | LED Indicators

Model No. USBG-4U3MLR2





- **Protect Your Equipment:** The 4-port USB 3.2 Gen 1 features 15kV ESD surge protection per port to keep your connected peripherals safe from harm.
- **Super Fast Speeds:** This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 4-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- **Upstream:** 1 USB port, Type B connector
- **Downstream:** 4 USB ports, Type A connectors
- Power Connector: 2-Pin Terminal Block
- Mounting Options: Wall, Surface, and DIN Rail
- Supply Current: 900mA USB Bus Power for Each Downstream Port

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Operating Temperature 0°C to 70°C (32°F to 158°F)

Environmental Storage Temperature -20°C to 85°C (-4°F to 185°F)

Humidity 5% ~ 95% (non-condensing)

ESD Protection 15KV Surge Protection for Each Port

Isolated/Surge Protected Yes

Performance Max Data Transfer Rate 5Gbps

Over Current Protection Y

Over Voltage Protection Y per buck

Chipset GL 3523

Charging Protocols BC 1.2, Charging Downstream Port (CDP)

LED Indicators Power

Per USB Port Current 900mA maximum

Product Information

Warranty 1 year from date of purchase

Input Voltage +7~48V DC

Over Current Protection Y

Over Voltage Protection Y per buck

Power Source 2-Pin Terminal Block, AC Adapter Not Included
Idle Consumption 7mA @ 12V Terminal Power, 9.4mA Bus Powered

External Power Required No

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

What's in the Box Package Contents

2-Pin Terminal Block, DIN Rail Clip(s), Hub, Screw Pack, USB-

A to USB-B Cable

USB Type USB 3.2 Gen 1

Upstream USB Ports 1 Type-B Female USB USB

Downstream USB Ports 4 Type-A Female USB

Isolated/Surge Protected Yes

Color Black

Item Dimensions (L × W ×

H)

 $4.50 \times 2.26 \times 1.03$ in.

Mechanical Item Weight 0.431 lbs.

Mounting Style Surface / Wall Mount, Din-Rail Mount

Ports 4 USB Ports

Material of Construction Galvanized Steel

Country of Origin Taiwan
Compliance

Certifications REACH, RoHS

UPC 736983900173

Series DRS-UH (DIN-Rail Series Hubs)
Other Data

Weight 1.243 lbs

Dimensions 9.000 × 6.625 × 1.625 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com