



USB 3.2 Gen 1 High Speed Isolation Adapter w/Screw Locking USB-B Port



Model No. CG-USB30ISO

The CG-USB30ISO is a USB 3.2 Gen 1 Super-Speed Isolation Adapter that complies with the Universal Serial Bus (USB) Specifications Revision 3.2 Gen 1 and offers up to a 5Gbps data rate. Since USB is the most popular external port for the devices to connect to PCs, the CG-USB30ISO provides an ideal solution to isolate your USB ports immediately and save your investments.

Interested? [LEARN MORE →](#)



[View more images here >](#)

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Environmental	Operating Temperature	0C to 55C
	Storage Temperature	-20°C ~ +80°C
Performance	Isolated/Surge Protected	Yes
	Max Data Transfer Rate	5Gbps
Hardware	LED Indicators	Power
Product Information	Warranty	1 year from date of purchase
	Power Source	AC Adapter Included, DC Barrel Jack 1.3mm ID × 3.5mm OD
Power	Adapter Input Current	0.5A
	Adapter Input Voltage	100~240V AC
	Adapter Output Current	2A
	Adapter Output Voltage	5V
	External Power Required	No
USB	USB Type	USB 3.2 Gen 1
	Upstream USB Ports	1 Type-B Female USB
	Downstream USB Ports	1 Type-A Female USB
	Isolated/Surge Protected	Yes
	Screw Lock Compatible	Yes
Mechanical	Color	Gray
	Item Dimensions (L × W × H)	3.24 × 1.74 × 0.87 in.
	Item Weight	0.125 lbs.
	UPC	045079163157
Other Data	Weight	0.532 lbs
	Dimensions	9.00 × 6.250 × 1.750 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

 **1-888-688-2188 (Toll free)**

 **sales@coolgear.com**