

## USB 3.2 Gen 1 High Speed Isolation Adapter w/Screw Locking USB-B Port



Model No. CG-USB30ISO



The CG-USB30ISO is a USB 3.2 Gen 1 Super-Speed Isolation Adapter that complies with the Universal Serial Bus (USB) Specifications Revision 3.2 Gen 1 and offers up to a 5Gbps data rate. Since USB is the most popular external port for the devices to connect to PCs, the CG-USB30ISO provides an ideal solution to isolate your USB ports immediately and save your investments.

Interested? LEARN MORE →



### Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

<sup>1</sup> 1-727-209-1300 (Local) **expert@coolgear.com** 



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

**Within every great machine, lives Coolgear.** - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

# PRODUCT SPECIFICATIONS

#### Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Operating Temperature 0C to 55C Environmental

Storage Temperature -20°C ~ +80°C

**Isolated/Surge Protected** Yes

Max Data Transfer Rate 5Gbps

Hardware LED Indicators Power

Product

**Performance** 

Warranty 1 year from date of purchase

**Power Source** AC Adapter Included, DC Barrel Jack 1.3mm ID × 3.5mm OD

Adapter Input Current 0.5A

Adapter Input Voltage 100~240V AC

Adapter Output Current 2A
Adapter Output Voltage 5V

**External Power Required** No

**USB Type** USB 3.2 Gen 1

Upstream USB Ports 1 Type-B Female USB

**USB Downstream USB Ports** 1 Type-A Female USB

**Isolated/Surge Protected** Yes **Screw Lock Compatible** Yes

**Color** Gray

Mechanical Item Dimensions (L × W ×

H)

 $3.24 \times 1.74 \times 0.87$  in.

Item Weight 0.125 lbs.

**UPC** 045079163157

Other Data Weight 0.532 lbs

**Dimensions**  $9.00 \times 6.250 \times 1.750 \text{ in}$ 

## Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

\*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com