

4 Port USB 3.2 Gen 1 Mini Powered Hub w/ ESD Surge Protection



Industrial Grade | +5V DC Input | Surge Protection | Surface Mountable | 5 Gbps

Model No. CG-U3MINI4P-BPH





- **Protect Your Equipment:** The 4-port hub features 15kV ESD surge protection to keep your connected peripherals safe from harm.
- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- Small-Scale Quality: Housed in a compact steel chassis, the 4-port hub is perfect for discreet installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Upstream: 1 USB port, Type B connector
- Downstream: 4 USB ports, Type A connectors
- **Power Connector:** DC Barrel 2.5mm ID × 5.5mm OD, Center Pin Positive
- Mounting Options: Wall & Surface

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.



[€] 1-727-209-1300 (Local) [∞] expert@coolgear.com

We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solutionoriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us. We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS



	• •• • •	
_ • • • •		0°C to 55°C (32°F to 131°F)
Environmental	Storage Temperature	-20 to 75°C (-4 to 167°F)
Performance	Humidity	5% ~ 95% (non-condensing)
	ESD Protection	15KV Surge Protection for Each Port
	Isolated/Surge Protected	
	Max Data Transfer Rate	5Gbps
	Over Current Protection	Y
	-	Y per buck
	Surge Protection	350W
	Chipset	GL 3510
Hardware	Charging Protocols	BC 1.2, Charging Downstream Port (CDP), Dedicated Charging Port (DCP), Samsung, Standard Downstream Port (SDP)
Product Information	Warranty	1 year from date of purchase
	Input Voltage	+5V DC
Power	Over Current Protection	Υ
	Over Voltage Protection	Y per buck
	Power Source	AC Adapter Not Included, DC Barrel Jack 2.5mm ID × 5.5mm OD
	Idle Consumption	57mA @ 5V / 35.6mA Bus Power
	External Power Required	No
Software	OS Support	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
What's in the Box	Package Contents	Hub, USB-A to USB-B Cable
	USB Type	USB 3.2 Gen 1
	Upstream USB Ports	1 Type-B Female USB
USB	Upstream USB Ports Downstream USB Ports	
USB	-	4 Type-A Female USB
USB	Downstream USB Ports	4 Type-A Female USB
USB	Downstream USB Ports Isolated/Surge Protected	4 Type-A Female USB Yes Black
USB Mechanical	Downstream USB Ports Isolated/Surge Protected Color Item Dimensions (L × W ×	4 Type-A Female USB Yes Black
	Downstream USB Ports Isolated/Surge Protected Color Item Dimensions (L × W × H)	4 Type-A Female USB Yes Black 2.87 (3.81 with flanges) × 1.86 × 1.13 in.
	Downstream USB Ports Isolated/Surge Protected Color Item Dimensions (L × W × H) Item Weight	4 Type-A Female USB Yes Black 2.87 (3.81 with flanges) × 1.86 × 1.13 in. 0.32 lbs.
	Downstream USB Ports Isolated/Surge Protected Color Item Dimensions (L × W × H) Item Weight Mounting Style	4 Type-A Female USB Yes Black 2.87 (3.81 with flanges) × 1.86 × 1.13 in. 0.32 lbs. Surface / Wall Mount 4 USB Ports
Mechanical	Downstream USB Ports Isolated/Surge Protected Color Item Dimensions (L × W × H) Item Weight Mounting Style Ports	4 Type-A Female USB Yes Black 2.87 (3.81 with flanges) × 1.86 × 1.13 in. 0.32 lbs. Surface / Wall Mount 4 USB Ports
	Downstream USB Ports Isolated/Surge Protected Color Item Dimensions (L × W × H) Item Weight Mounting Style Ports Material of Construction	4 Type-A Female USB Yes Black 2.87 (3.81 with flanges) × 1.86 × 1.13 in. 0.32 lbs. Surface / Wall Mount 4 USB Ports Galvanized Steel
Mechanical	Downstream USB Ports Isolated/Surge Protected Color Item Dimensions (L × W × H) Item Weight Mounting Style Ports Material of Construction Country of Origin	4 Type-A Female USB Yes Black 2.87 (3.81 with flanges) × 1.86 × 1.13 in. 0.32 lbs. Surface / Wall Mount 4 USB Ports Galvanized Steel Taiwan
Mechanical	Downstream USB Ports Isolated/Surge Protected Color Item Dimensions (L × W × H) Item Weight Mounting Style Ports Material of Construction Country of Origin Certifications	4 Type-A Female USB Yes Black 2.87 (3.81 with flanges) × 1.86 × 1.13 in. 0.32 lbs. Surface / Wall Mount 4 USB Ports Galvanized Steel Taiwan RoHS
Mechanical	Downstream USB Ports Isolated/Surge Protected Color Item Dimensions (L × W × H) Item Weight Mounting Style Ports Material of Construction Country of Origin Certifications UPC	4 Type-A Female USB Yes Black 2.87 (3.81 with flanges) × 1.86 × 1.13 in. 0.32 lbs. Surface / Wall Mount 4 USB Ports Galvanized Steel Taiwan RoHS 045079163300
Mechanical	Downstream USB Ports Isolated/Surge Protected Color Item Dimensions (L × W × H) Item Weight Mounting Style Ports Material of Construction Country of Origin Certifications UPC Series	4 Type-A Female USB Yes Black 2.87 (3.81 with flanges) × 1.86 × 1.13 in. 0.32 lbs. Surface / Wall Mount 4 USB Ports Galvanized Steel Taiwan RoHS 045079163300 WKS-UH (Workstation Series Hubs)

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

- ⁽ <u>1-888-688-2188 (Toll free)</u>
- sales@coolgear.com