



USB 3.1 Type-C & A 4 Port Metal Hub w/DIN Rail Clip & ESD Surge Protection



Mountable USB 3.1 Dual Type 4 Port Hub

Model No. CG-UC4U3ML



The newly redesigned Coolgear USB 3.1 Type-C 4 port metal industrial hub complies with USB 3.1 Gen1 standards capable of up to 5Gbps data transmission. It supports 7-48V through its 2-wire plug connector for extra power to hungry devices (power adapter sold separately). The new, redesigned Coolgear USB 3.1 Gen1 Type-C hub has 2 USB-C and 2 USB-A ports for connection versatility.

- USB 3.1 Gen1 compliant – allows up to 5Gbps of data transfer.
- Accepts 7-48V additional power through the 2-wire plug.
- Backward compatible with USB 2.0 and 1.1 speeds.
- DIN Rail mounting option keeping your cables out of the way.

Interested? [LEARN MORE →](#)



[View more images here >](#)

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?
[View CAD Models, Data sheet and Drawings here >](#)



Environmental	Operating Temperature	0C to 70C
	Power	
	Input Voltage	+7~48V DC
USB	USB Type	USB 3.1
	Color	Black
	Mounting Style	Din-Rail, Surface Mount
Mechanical	Ports	4 USB Ports
	Compliance	TAA Hubs
Compliance	Connector	USB Type-A Female, USB Type-C Female
	Weight	1.243 lbs
Other Data	Dimensions	9.000 × 6.625 × 1.625 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

 [1-888-688-2188](tel:1-888-688-2188) (Toll free)

 sales@coolgear.com