

7 Port USB 3.2 Gen 1 Type-C Hub w/ ESD Surge Protection & USB-C Upstream



Industrial Grade | +7~48V DC Input | Surge Protection | Surface Mountable | DIN Rail | 5 Gbps

Model No. CG-7PU313C





- **Protect Your Equipment:** The 7-port Type-C hub supports 15KV ESD surge protection for each port to keep your connected peripherals safe from harm.
- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 7-port hub is perfect for workstations installations in offices, labs, warehouses, and other industrial applications.
- Upstream: 1 USB-C port
- Downstream: 5 USB-A connectors, 2 USB-C port
- Power Connector: 2-Pin Terminal Block
- Mounting Options: Wall, Surface, & DIN Rail

Interested? LEARN MORE >



Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Operating Temperature 0°C to 55°C (32°F to 131°F)

Environmental Storage Temperature -20°C to 85°C (-4°F to 185°F)

Humidity 5% ~ 95% (non-condensing)

ESD Protection 15KV Surge Protection for Each Port

Isolated/Surge Protected Yes

Performance Max Data Transfer Rate 5Gbps

Over Current Protection Y

Over Voltage Protection Y per buck
Chipset GL 3523

Hardware Charging Protocols

Apple 2.4A, Charging Downstream Port (CDP), Dedicated

Charging Port (DCP)

LED Indicators Power

Product Information

Warranty 1 year from date of purchase

Input Voltage +7~48V DC

Over Current Protection Y

Over Voltage Protection Y per buck

Power Source 2-Pin Terminal Block, AC Adapter Not Included

Idle Consumption 10.33mA @ 12V Terminal Power, 18.51mA Bus Powered

External Power Required No

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

What's in the Box Package Contents

2-Pin Terminal Block, DIN Rail Clip(s), Hub, Screw Pack, USB-

A to USB-B Cable

USB Type USB 3.1

Upstream USB Ports 1 Type-C Female USB USB

Downstream USB Ports 5 Type-A Female USB, 2 Type-C Female USB

Isolated/Surge Protected Yes

Color Black

Item Dimensions (L × W ×

5.23 × 2.42 × 1.43 in.

Mechanical Item Weight 0.650 lbs.

H)

Mounting Style Surface / Wall Mount, Din-Rail Mount

Ports 7 USB Ports

Material of Construction Galvanized Steel

Country of Origin Taiwan Compliance

Certifications TAA Hubs, CE, FCC, RoHS

Connector USB Type-A Female, USB Type-C Female

UPC 045079158771

Other Data Series <u>DRS-UH (DIN-Rail Series Hubs)</u>

Weight 1.162 lbs

Dimensions 9.625 × 6.562 × 2.125 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com