



4 Port USB 3.2 Gen 1 Type-C Hub w/ ESD Surge Protection



Industrial Grade | +7~48V DC Input | Surface Mountable | DIN Rail | 5 Gbps | Screw Lock

Model No. CG-4PU31C1B1



[View more images here >](#)

- **Protect Your Equipment:** The 4-port Type-C hub supports 15KV ESD surge protection for each port to keep your connected peripherals safe from harm.
- **Super Fast Speeds:** This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with 2.0 / 1.1.
- **Superior Build Quality:** Housed in a rugged steel chassis with built in mountable flanges, the 4-port hub is perfect for workstations installations in offices, labs, warehouses, and other industrial applications.
- **Upstream:** 1 USB port, Type B connector
- **Downstream:** 1 USB ports, Type C connectors & 3 USB ports, Type A connectors
- **Power Connector:** 2-Pin Terminal Block
- **Mounting Options:** Wall, Surface, & DIN Rail

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Environmental	Operating Temperature	0°C to 55°C (32°F to 131°F)
	Storage Temperature	-20 to 75°C (-4 to 167°F)
	Humidity	5% ~ 95% (non-condensing)
	ESD Protection	15KV Surge Protection for Each Port
Performance	Isolated/Surge Protected	Yes
	Max Data Transfer Rate	5Gbps
	Over Current Protection	Y
	Over Voltage Protection	Y per buck
Hardware	Chipset	GL 3523
	Charging Protocols	Charging Downstream Port (CDP), Dedicated Charging Port (DCP)
	LED Indicators	Power
Product Information	Warranty	1 year from date of purchase
	Input Voltage	+7~48V DC
	Over Current Protection	Y
Power	Over Voltage Protection	Y per buck
	Power Source	2-Pin Terminal Block, AC Adapter Not Included
	External Power Required	No
Software	OS Support	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
What's in the Box	Package Contents	2-Pin Terminal Block, DIN Rail Clip(s), Hub, Screw Pack, USB-A to USB-B Cable
USB	USB Type	USB 3.2 Gen 1
	Upstream USB Ports	1 Type-B Female USB
	Downstream USB Ports	1 Type-C Female USB, 3 Type-A Female USB
	Isolated/Surge Protected	Yes
Mechanical	Color	Black
	Item Dimensions (L × W × H)	4.50 × 2.26 × 1.03 in.
	Item Weight	0.381 lbs.
	Mounting Style	Surface / Wall Mount, Din-Rail Mount
Compliance	Ports	4 USB Ports
	Material of Construction	Galvanized Steel
	Country of Origin	Taiwan
	Certifications	REACH , TAA Hubs , RoHS
Other Data	Connector	Type-C
	UPC	045079158429
	Series	DRS-UH (DIN-Rail Series Hubs)
	Weight	0.937 lbs
	Dimensions	9.625 × 6.625 × 2.125 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

📞 **1-888-688-2188 (Toll free)**

✉ **sales@coolgear.com**