



# USB-C to USB-A Power Delivery Adapter w/Mounting Kit



Compact USB-C to A Power Delivery

Model No. CG-UCUSBPD



[View more images here >](#)

Backward compatible with USB 3.0 and 1.1, the USB 3.1 Power delivery adapter is compliant with Gen1 and 2 of the USB 3.1 specification. The USB-C power delivery adapter acts as a PD source for the upstream USB-C port.

- Compliant with USB 3.1 Gen1 and Gen2
- Supports USB PD (power delivery), Works as a Source
- DC Power Input: 20V DC, from DC Jack or Terminal Blocks
- Supports Source PDO's (Power Data Object): 20V/5A, 14.5V/2A, 12V/3A and 5V/3A

\*20V/5A profile will only enumerate with an emarker cable capable of this power rating(sold separately), 65watt max Output DC adapter included. Higher output DC adapter must be purchased separately to attain higher than 65 watt output rating. \* Notice: This product does NOT support USB-C DisplayPort (DP/Video Alt Mode) and is intended for data and power functionality only.

**Interested? LEARN MORE →**

## Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ **1-727-209-1300** (Local) ✉ **expert@coolgear.com**



**We Speak Your Speak** - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

**We're Ready For Integration, Every Time.** - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

**Within every great machine, lives Coolgear.** - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

# PRODUCT SPECIFICATIONS

Looking for product documentation?  
[View CAD Models, Data sheet and Drawings here >](#)



Compliance	Certifications	<a href="#">REACH</a> , <a href="#">RoHS</a> , <a href="#">TAA</a>
Physical Characteristics	Color	Gray
	Mounting Style	Din-Rail (Optional Bracket), Wall Mount
	Ports	2 USB Ports
	Screw Lock Compatible	Yes
Software	OS Support	OS Independent
	Connector	Terminal Block, Type-C, USB Type-A Female
	UPC	045079158894
Other Data	USB Interface	Screw Lock, USB 3.1
	Weight	1.325 lbs
	Dimensions	9.625 × 6.500 × 2.250 in

### Ready to Buy? Let's get to work!

[Purchase order](#) lets set you up.

[Online with Credit card](#) Orders shipped same day!

\*orders placed prior to 3:30pm EST

[1-888-688-2188](tel:1-888-688-2188) (Toll free)

[sales@coolgear.com](mailto:sales@coolgear.com)