



Chargeit! Mini 75W Dual Port USB-A & USB-C PD Charger w/ PPS & QC4.0 Support



Model No. CG-PD60PPS



[View more images here >](#)

Industrial Grade | +9~24V DC Input | Over Voltage & Current Protection | Surface Mountable

- **Simultaneous Charging:** Charge 2 iPads, iPhones or other USB-charged in charge mode devices, while the built in PD chipset dynamically detects devices to deliver optimum power level for maximum battery life and performance.
- **Quick Charging:** Provides up to 75W of combined charging. The USB-A port supports QC 3.0 while the USB-C port supports QC 4.0.
- **PPS:** Programmable power supply capability allows for small step-wise changes in voltage, current, and for constant current charging (with gradual voltage increase), followed by constant voltage charging (with gradual current reduction).
- **Superior Build Quality:** Housed in a rugged metal chassis, the 2-port charger hub is perfect for installations in offices, labs, warehouses, classrooms, heavy machinery, automation equipment, and other industrial applications
- **Downstream:** 1 USB Type-A QC Port, 1 USB Type-C PD Screw-Lock Compatible Port
- **Power Connector:** 2-Pin Terminal Block
- **Mounting Options:** Wall & Surface
- **LED Indicators:** Power

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ **1-727-209-1300** (Local) ✉ **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all Coolgear | Charging & Connectivity Experts Visit coolgear.com/support for any questions & inquires.
www.coolgear.com

manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Environmental	Identifier	Product Type	Adapters > USB C Adapters > Power Delivery
		Operating Temperature	0°C to 55°C (32°F to 131°F)
		Storage Temperature	-20 to 75°C (-4 to 167°F)
		Humidity	5% ~ 95% (non-condensing)
Performance		Over Current Protection	Y
		Over Voltage Protection	Y
Hardware		Charging Protocols	Apple 2.4A, Dedicated Charging Port (DCP), QC3.0, QC4.0, Samsung
		LED Indicators	Power
Product Information		Warranty	1 year from date of purchase
		Input Voltage	+9~24V DC
Power		Over Current Protection	Y
		Over Voltage Protection	Y
		Power Source	2-Pin Terminal Block
What's in the Box		Package Contents	2-Pin Terminal Block, USB Charger
PD Profile Support		Voltage Profiles	5V/3A, 7V/2.5A, 9V/3A, 12V/3A, 15V/3A, 20V/2.99A
USB		USB Type	Type-C
		Downstream USB Ports	1 Type-A Female USB, 1 Type-C Female USB
		Color	Black
		Item Dimensions (L × W × H)	3.48 × 2.00 × 1.03 in.
Mechanical		Item Weight	0.293 lbs.
		Mounting Style	Surface / Wall Mount
		Ports	2 USB Ports
		Material of Construction	Steel
Compliance		Country of Origin	China
		Certifications	RoHS
		Chip Model	Cypress CCG3PA
Other Data		Model No.	CG-PD60PPS
		UPC	045079161368
		Weight	0.281 lbs
		Dimensions	3.48 × 1.99 × 1.03 in

Ready to Buy? Let's get to work!

[Purchase order](#) lets set you up.

[Online with Credit card](#) Orders shipped same day!

*orders placed prior to 3:30pm EST

[1-888-688-2188 \(Toll free\)](tel:1-888-688-2188)

sales@coolgear.com