



# USB to RS-232 Isolated TTL | CMOS 5ft. Adapter Cable w/ TB



Model No. **USB-232TTLMOS-  
IS**



- **Expand Your Serial Capabilities:** Connect your legacy serial device through a USB-A port to add legacy functionality to newer technologies with no serial port connections.
- **Safe Connections:** Designed with a unique system load reduction feature, the Mini USB to Serial Adapter also offers 2,500Vrms Isolation for connected devices.
- **Plug-&-Play:** The adapter's power is drawn from a USB connection for ease of access and is compatible with Windows (up to Win 11), Mac OS, and Linux.
- **COM Retention:** COM Ports are fully configurable, and after reboots, port assignments are preserved.
- **Upstream:** 1 USB port, Type A Male Connector
- **Downstream:** 5-Pin Terminal Block

**Interested? [LEARN MORE](#) →**

## Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ [expert@coolgear.com](mailto:expert@coolgear.com)



**We Speak Your Speak** - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

**We're Ready For Integration, Every Time.** - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

**Within every great machine, lives Coolgear.** - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

# PRODUCT SPECIFICATIONS

Looking for product documentation?  
[View CAD Models, Data sheet and Drawings here >](#)




<b>Power</b>	<b>Adapter Power</b>	USB Bus Powered
	<b>External Power Required</b>	No
<b>Compliance</b>	<b>Country of Origin</b>	Taiwan
	<b>Color</b>	Black
<b>Physical Characteristics</b>	<b>Item Dimensions (L x W x H)</b>	1.77 x 1.65 x 1.15 in.
	<b>Item Weight</b>	3.7 oz.
	<b>Length</b>	5ft
	<b>Material of Construction</b>	Plastic
	<b>RS Signals</b>	TxD, RxD, VOUT, VIN, GND
<b>Serial Attributes</b>	<b>Serial Standards</b>	RS232
	<b>Baud Rate</b>	921.6K bps
	<b>Data Bits</b>	7, 8
	<b>Parity</b>	None, Even, Odd, Mark, Space
	<b>Stop Bits</b>	1, 2
	<b>Flow Control</b>	Hardware (RTS, CTS), XON/XOFF
	<b>Serial Ports</b>	1
<b>Software</b>	<b>OS Support</b>	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
<b>Environmental</b>	<b>Operating Temperature</b>	-40 to 85 C
	<b>Storage Temperature</b>	-40°C to 85°C (-40°F to 185°F)
	<b>Humidity</b>	5% ~ 95% (non-condensing)
<b>Product Information</b>	<b>Warranty</b>	1 year from date of purchase
<b>Performance &amp; Safety</b>	<b>Isolated/Surge Protected</b>	Yes
<b>Other Data</b>	<b>Connector</b>	5-Pin Terminal Block
	<b>USB Interface</b>	USB 2.0
	<b>Weight</b>	0.412 lbs
	<b>Dimensions</b>	8.937 x 6.312 x 1.612 in

## Ready to Buy? Let's get to work!

[Purchase order](#) lets set you up.

[Online with Credit card](#) Orders shipped same day!

\*orders placed prior to 3:30pm EST

 [1-888-688-2188 \(Toll free\)](tel:1-888-688-2188)

 [sales@coolgear.com](mailto:sales@coolgear.com)