



Model: USBG-2COM-PRO

2 Port USB to RS-232 /422 / 485 Auto Setup Adapter for Windows Linux and Mac

USB to RS-232 Industrial Pro Line serial adapter USB-2COM-PRO supports RS232, RS422, and RS485 with standard DIN-Rail mounting.



Specifications

Serial Interface	RS232/422/485 selected by software
Ports	2
Speed	Up to 921.6kbps RS232, up to 3Mbps RS422/RS485
Available Modes	RS232 full duplex, RS422 full duplex, RS485 4 wire, full duplex, RS485 2 wire, half duplex, with echo, RS485 2 wire, half duplex, without echo
Signals	RS232 TxD, RxD, RTS/CTS, DTR, DSR, DCD, RI, GND RS422 Tx+/-, Rx+/-, GND RS485 2 wire Data+/-, GND RS485 4 wire Tx+/-, Rx+/-, GND
USB Interface	USB 2.0
Power	USB Bus powered, no external power supply
Driver	Windows XP, 2003 Server, Vista, Linux (Kernel 2.4 and up built-in)
Connectors	2 DB9 male, terminal blocks for RS422/485
Dimensions	115 x 85 x 26 mm (WxLxH), 137 x 90 x 23 mm (with DB9 connector and ears)
Driver (OS) Support	Windows 7, Vista, 2003, XP (WHQL certified) and 2000, Linux Kernel 2.4 and up built-in support
Environmental	Operating Temperature 0 to 55 °C (32 to 131 °F) Operating Humidity 5 to 95% RH Storage Temperature -20 to 75 °C (-4 to 167 °F)

Features

- Jumper less, no DIP switches
- USB 2.0 interface
- DIN-Rail mountable
- RS232/422/485 DB9 male port
- Terminal block
- Speed up to 3000kbps
- No external power supply
- Metal case

Product Information

- Product Name:** USBG-2COM-PRO
- Packing List:** USBG-2COM-PRO, USB cable 0,9m, CD, English Documentation
- Optional Accessories:** DK 35A - DIN-Rail mounting kit