



Model: USBG-4COM-PRO

4 Port USB to RS-232/422/485 Auto Setup Adapter for Win – Linux – Mac

High-speed 4 Port USB to RS-232, RS422, and RS485 Serial Adapter with 128 byte FIFO memory chip. Use with newer computers where serial ports no longer exist. Through an available USB port experience speed settings of up to 500,000BPS in communication.



Specifications

Serial Interface	RS232/422/485 selected by software
Ports	4
Speed	Up to 921.6kbps RS232, up to 3Mbps RS422/RS485
Available Modes	RS232 full duplex, RS422 full duplex, RS485 4 wire, full duplex, RS485 2 wire, half duplex, with echo, RS485 2 wire, half duplex, without echo
Signals	RS232 TxD, RxD, RTS/CTS, DTR, DSR, DCD, RI, GND RS422 Tx+/-, Rx+/-, GND RS485 2 wire Data+/-, GND RS485 4 wire Tx+/-, Rx+/-, GND
USB Interface	USB 2.0
Power	External power supply 5V DC
Driver	Windows XP, 2003 Server, Vista, Linux (Kernel 2.4 and up built-in)
Connectors	4 DB9 male
Dimensions	172 x 95 x 29mm (W x L x H), 184 x 99 x 29 mm with DB9 connector and ears
Environmental	Operating Temperature 0 to 55 °C (32 to 131 °F) Operating Humidity 5 to 95% RH Storage Temperature -20 to 75 °C (-4 to 167 °F)

Features

- Jumper less, no DIP switches
- USB 2.0 interface
- DIN-Rail mountable
- RS232/422/485 DB9 male port
- Speed up to 3000kbps
- External power supply
- Metal case

Product Information

Product Name:	USBG-4COM-PRO
Packing List:	USB-4COM-PRO, USB cable 0,9m, Power cord, CD, English Documentation
Optional Accessories:	N/A