



Model: USBG-COM-PRO

USB to RS-232 422 485 Auto Setup Adapter
Windows Linux and Mac

USB to RS-232 Industrial Single Port RS-232/422/485 Adapter.
Rugged metal case for industrial applications and optional 5-pin terminal block for flexibility of serial connection.



Specifications

Serial Interface	RS232/422/485 selected by software
Ports	1
Speed	Up to 921.6kbps RS232, up to 3Mbps RS422/RS485
Available Modes	RS-232 full duplex, RS422 full duplex, RS485 4 wire, full duplex, RS485 2 wire, half duplex, with echo, RS485 2 wire, half duplex, without echo
Signals	RS232: TxD, RxD, RTS/CTS, DTR, DSR, DCD, RI, GND RS422: Tx+/-, Rx+/-, RTS+/-, CTS+/-, GND RS485 4-wire: Tx+/-, Rx+/-, GND RS485 2-wire: Data+/-, GND
USB Interface	USB 2.0
Power	USB Bus powered, no external power supply
Driver	Windows XP, 2003 Server, Vista, Linux (Kernel 2.4 and up built-in)
Connectors	1 DB9 male, terminal blocks for RS422/485
Dimensions	57 x 72 x 22 mm (WxLxH), 82 x 77 x 22 mm (with DB9 connector and ears)
Environmental	Operating Temperature 0 to 55 °C (32 to 131 °F) Operating Humidity 5 to 95% RH Storage Temperature -20 to 75 °C (-4 to 167 °F)

Features

- Jumper less, no DIP switches
- USB 2.0 interface
- DIN-Rail mountable
- RS232/422/485 DB9 male port
- Speed up to 3000kbps
- No external power supply
- Metal case

Product Information

Product Name: USBG-COM-PRO
Packing List: USBG-COM-PRO Adapter, USB cable 0,9m, CD, English Documentation
Optional Accessories: N/A