

Technical Data Sheet

USB RS-232 Adapter Industrial Isolated – Surge Protected FTDI Chip

Model Number: USBG-SSRS1



The USB-SSRS1 USB to serial conversion cable is designed for PC, thin client, or server to provide an instant Isolation and Surge Protection COM port expansion via the Universal Serial Bus (USB). The USB-SSRS1 provides the scalability to quickly adapt to new USB technologies. Multiple modules can be added to a single USB interface allowing you to add WAN connectivity as needed.

Features

- Fully compatible with USB 1.1 and Forward compatible with USB 2.0.
- Supports 1 DB9-Male UART Serial port.
- Built-in 2500Vrms Optical Isolation Circuits.
- Built-in 500W Bi-direction Surge Protection Circuits.
- Baud Rate: 300bps to 460Kbps
- Automatic recognition of the adapter, driver install is automatic.
- Screw locking mechanism for secure tightening.
- Bus Powered

Product Information

- Model Number: <u>USBG-SSRS1</u>
- Packing List:
 - USB to RS232 Isolated Adapter
 - Paper installation Guide
 - o Driver Disc
- Optional Accessories: N/A

Specifications



OVERVIEW Product Type USB to Serial RS-232 Adapter (USB 2.0 backward compatible to USB 1.1) **Electrical Protections** Optical Isolation: 2500Vrms / 500W Bi-Directional Surge Protection Plastic Construction FTDI Chip Applications Data Centers, Automotive peripheral installation, Machine Equipment, Kiosk, Office, and others Certs / Compatibility RoHS, Reach 181, TAA CONNECTIONS USB Type-A Male Connector Serial 1 (Screw lock compatible) DB-9 Male Connector SERIAL COMMUNICATION RS-232 Data Signal Supports 3-wire signals TxD, RxD, GND Data Bits 78

| Data Bits | 7, 8 |
|-----------------------|----------------------------------|
| Stop Bits | 1, 2 |
| Parity | None, Odd, Even, Mark, Space |
| Baud Rate | 300 bps to 921.6 Kbps |
| AVAILABLE POWER MODES | |
| Mode 1 | Bus powered only |
| ENVIRONMENTAL | |
| Operating Temperature | 0 to 55°C (32 TO 131°F) |
| Operating Humidity | 5 to 95% RH |
| Storage Temperature | -20°C to 85°C (-4 to 185° F) |
| DIMENSIONS | |
| Length | 1.77 in |
| Width | 1.63 in |
| Height | 0.86 in |
| Cable Length | 6FT. |
| OS SUPPORT | |
| Windows | Windows 7, Windows 8, Windows 10 |
| Other | Linux and Mac OS 10.X |
| Downstream Ports | N/A |
| WARRANTY | |
| Warranty Period | 1 year from date of purchase |
| CoolGear Inc | |



| PRODUCT URL | |
|-------------------------|---|
| USBG-SSRS1 Product Page | https://www.coolgear.com/product/usb-rs-232-adapter-industrial-isolated-and-surge-protected-ftdi-chip |

© 2017 Coolgear, Inc. All Rights Reserved. All products and accompanying digital documentation including images are the property and / or trademarks of Coolgear Inc. Coolgear Inc. are continuously improving upon its products. Product specifications are subject to change without notice.