



Model: USBG-8COM-PRO

8 Port USB 2.0 to RS232, RS422, RS485 Auto Setup Adapter

The USBG-8COM-PRO 8 Port USB 2.0 to RS232, RS422, and RS485 Auto Setup serial adapter is an industrial-grade, software configurable adapter with transfer speeds of 921.6kbps RS232 and up to 3Mbps RS422 or RS485.



Specifications

Serial Interface	RS232/422/485 selected by software
Ports	8
Speed	Up to 921.6kbps RS232, up to 3Mbps RS422/RS485
Available Modes	RS232 full duplex RS422 full duplex RS485 4 wire, full duplex RS485 2 wire, half duplex, with echo RS485 2 wire, half duplex, without echo
Signals	RS232 TxD, RxD, RTS/CTS, DTR, DSR, DCD, RI, GND RS422 Tx+/-, Rx+/-, GND RS485 2 wire Data+/-, GND RS485 4 wire Tx+/-, Rx+/-, GND
USB Interface	USB 2.0
Power	Built-in power supply 110-240V AC 47-63 Hz, 25VA
Driver	Windows XP, 2003 Server, Vista, Linux (Kernel 2.4 and up built-in)
Connectors	8 DB9 male
Dimensions	258 x 149 x 45 mm (WxLxH), 278 x 155 x 46 mm with DB9 & DIN-Rail ears 19" IHU Rack mount
Environmental	Operating Temperature 0 to 55 °C (32 to 131 °F) Operating Humidity 5 to 95% RH Storage Temperature -20 to 75 °C (-4 to 167 °F)

Features

- Jumper less, no DIP switches
- USB 2.0 interface
- DIN-Rail mountable
- RS232/422/485 DB9 male port
- Speed up to 3000kbps
- Built-in power supply
- Metal case

Product Information

Product Name:	USBG-8COM-PRO
Packing List:	USB-8COM-PRO, USB cable 0,9m, AC Power cord, CD, English Documentation
Optional Accessories:	N/A