






NOTE: All materials compliant with RoHS, REACH and PrO65 standards

REV.	DATE	ECN NO.	DESCRIPTION
A0	2021. 04. 17	/	/



PIN ASSIGNMENT



Testing Requirements :

- 100% real machine screen test
- Insulation resistance : 10MΩ MIN (300DC/0.01s).
- Conduction impedance : 2Ω MAX.

NO.	NAME	SPECIFICATIONS	Q' TY	UNIT
5	OUTER MOLDING	Black PVC 40P	10	G
4	INNER MOLDING	MG70 LDPE transparent color	10	G
3	CONNECTOR	USB3.0 B/M connector blue core/nickel plated iron case/pin gold plated	1	PCS
2	CONNECTOR	USB3.0A /M connector blue core/nickel plated iron case/pin gold plated	1	PCS
1	CABLE	USB3.0 (28AWG. 7/0. 12TC*1P+D7/0. 12TC+AL+HM) *2+ (28AWG. 7/0. 12TC) *1P+ 24AWG 7/0. 2TC*2C+ADB+PVC OD:5.5MM BLACK 304.8mm	AR	MM

	MODEL #:	USB3.0-ABM-1FT
	PAGE:	1 / 1
	NOTES:	
DRAW:		
DATE:		SCALE: 1mm = 1mm
UNIT: mm	TOLERANCE: +/- 0.15 mm	
SITE: coolgear.com	CONTACT: support@coolgear.com	

F
E
D
C
B
A

8 7 6 5 4 3 2 1