



Model: USB2-4COM-M-CBL

**4-Port RS-232 USB to Serial Adapter Octopus Cable
 DIN Rail**

Compact Industrial RS232 Serial Adapter bringing 4 DB9 RS232 Ports from one simple connection. Helps expand your system COM ports without the use of additional resources



Specifications

Compliance	USB 1.1/2.0 Compatible
Serial Interface	RS232
Ports	4 DB9 Male
Speed	480 Mbps, High Speed USB
Available Signals	RS232 TxD, RxD, RTS/CTS, DTR, DSR, DCD, RI, GND
Communication Parameters	Data Bits: 7, 8 Stop Bits:1, 1.5, 2 Parity: None, Even, Odd, Space, Mark Flow Control: RTS/CTS, XON/XOFF
Baud Rate	300 bps to 921.6Kbps
Power	USB Bus powered, must have 5V .500mA to operate
Protection	10KV
Connectors	DB9 male Breakout Cable: DB37-to-4 DB9 cable, 30cm , or DB37-to-4 DB25 cable,30cm
Dimensions	122.22mm(L) x 69.85mm(W) x 31.75mm(H)
Driver (OS) Support	Windows 7, Vista, 2003, XP (WHQL certified) and 2000 Linux Kernel 2.6.3.1 and up built-in support
Environmental	Operating Temperature: 0 to 55 °C (32 to 131 °F) Operating Humidity: 5 to 95% RH Storage Temperature: -20 to 75 °C (-4 to 167 °F) Safety Approvals: CE, FCC

Features	Product Information	
<ul style="list-style-type: none"> • Adds 4 industrial RS232 Com ports to your system • Supports DIN Rail Mounting • Hardware/software flow control • 128 byte transmit FIFO & 384 byte receive FIFO • USB port powered • Installed as a standard Windows COM Port 	Product Name:	USB2-4COM-M-CBL
	Packing List:	Serial Adapter, 30cm Breakout Cable, DIN-Rail Bracket/screws, Driver Disk
	Optional Accessories:	N/A