



Model: CG-232485CBO

2 Port RS232/422/485 Serial to USB 2.0 Combo Adapter

2-Port serial adapter supports the use of one or two serial protocols simultaneously making it very versatile for many COM applications.

RoHS

Specifications	
Serial Interface	RS232/422/485 selected by DIP Switch Controls
Ports	1 USB type-B female, 2 DB9 Male
Speed	Up to 921.6kbps
Available Modes	RS232 Mode, RS422 Mode, RS485 2-wire Mode, RS485 4-wire Mode
Signals	RS232 TxD, RxD, RTS/CTS, DTR, DSR, DCD, RI, GND RS422 Tx+/-, Rx+/-, GND RS485 2 wire Data+/-, GND RS485 4 wire Tx+/-, Rx+/-, GND
USB Interface	USB 2.0
Power	USB Bus powered, must have 5V .500mA to operate
Driver	Windows 2000, XP, 2003 Server, Vista, OS X, Linux
Connectors	2 DB9 male, 1 USB Type-B Female to computer
Dimensions	101.6mm(L) x 87.29mm(W) x 23.81mm(H), 112.71x 87.29 x 2381 mm (with mounting ears)
Driver (OS) Support	Windows 7, Vista, 2003, XP, and 2000, Linux, OS X
Environmental	Operating Temperature 0 to 55 °C (32 to 131 °F) Operating Humidity 5 to 95% RH Storage Temperature -20 to 75 °C (-4 to 167 °F)

Features	Product Information	
<ul style="list-style-type: none"> Provides 2 RS232/422/485 Serial Ports or combination Supports Hot-Plugging Provides 2 DSUB-9 Connectors Supports USB 2.0 High-Speed data rate 480Mbps Baud Rate or 921.6Kbps Supports USB Bus Power 	Product Name:	CG-232485CBO
	Packing List:	Serial to USB 2.0 Combo Adapter, User Manual, Driver Disk, 6ft USB Cable
	Optional Accessories:	N/A