

CG-PCIX4IPS PCIe to PCIX4 Expansion Box with Internal Power Supply

The CG-PCIX4IPS PCI Express to Quad PCI Slots Expansion Box is specially designed to expand 4 extra PCI slots from a PCI Express Slot. It is connected to a host PC with a PCIe adapter card, a cable, an ATX chassis bracket and the slot expansion board. The board is internally powered by the standard ATX power supply within the chassis. It provides instant PCI bus expansion via the PCI Express Bus (PCIe).

PCI Express provides a scalable, high-speed, serial I/O bus that maintains backward compatibility with PCI applications and drivers. Its architecture defines a high-performance, point-to-point, scalable, serial bus at speed of 250Mbytes/sec to 4GBytes/sec (and 8Gbytes/sec in the future).

The PCI slots of the box are fully Plug-and-Play compatible and no IRQ and I/O address conflict problems. The CG-PCIX4IPS provides the scalability to quickly adapt to new PCI Express technologies for legacy PCI add-in cards. It allows you to add PCI connectivity as needed. The complete product line offer many choices help you to expand and make your I/O resource grow with your requirements.



Features & Specifications

Features

Provides 4 PCI Slots

- Full x1 PCI Express Throughput, 250Mbytes/sec
- Fully Compliant with PCI Express Base Specifications, Revision 1.0a
- Expands 4 PCI 32-bit 33MHZ Slots over PCI Express Slot
- PCI Slots are fully Compliant PCI Bus Rev. 2.3
- Supports both 5V and 3.3V Add-in Cards
- Supports Cable Length up to 2 meters
- Low Profile Version is Available with Short Bracket
- PCI Express card
- Builds in 220-Watt Standard ATX Power Supply
- Builds in Cooling Fan
- Extended Virtual Channel (VC) Support
- Includes a Second VC for Quality-of-Service and Isochronous Applications
- Active State Link Power Management Support

Specifications

Fully compliant with x1 PCI Express Base

PCI Slots

- Provides four 32-bit/33MHZ PCI Slots
- Fully PCI Specifications 2.3 Compliant
- Supports both 5V and 3.3V Fault Tolerance Option
- Builds in 220-Watt Internal ATX Power
- Advanced PCI Isochronous Windows for Memory Space Mapping to a Specified Traffic Class

I/O Hardware

Host connector: One 24-pin connector for PCI Express Host Cable

ATX 2x12 Power Connector: One standard 2x 12 ATX Power Input Connect to be powered by standard ATX PC Power Supply.

Environmental Specifications

Operating Temperature: 0 to 55°C (32 to 131°F), 10% to 90% relative humidity (non-condensing)

Storage Temperature: -40 to 75°C (-40 to 167°F), 5% to 95% relative humidity (non-condensing)

Form Factor

10.41 x 8.66 x 5.51" (25 x 22 x 14cm)

