

Technical Data Sheet Rev 05.221130

# 6 port Managed USB 2.0 Hub w/ 15KV ESD Surge Protection

Model Number: CG-6PU2MGD



## Features

- Compliant with USB Specification 2.0
- Supports 480Mbps (High speed), 12Mbps (Full-speed) and 1.5Mbps (Low-speed) Speed
- Software Manageable Bus power for each Port
- Supports 15KV ESD Level 4 Protection for Each Port
- Supports +7~48V DC Wide Range Input Power

## Package Contents

- 2-Pin Terminal Block
- DIN rail bracket
- Hub
- Screw Lock USB Cable
- Screw Pack

## Specifications

### OVERVIEW

Model No	CG-6PU2MGD
Product Type	USB Hub
Compliance	REACH   RoHS   TAA
UPC	045079163089
Country of Origin	Taiwan
LED indicators	Power
Chipset	GL852GT
Electrical Protections	15kv

### PHYSICAL

Ship Weight (lbs)	1.09 lbs
Ship Weight (kg)	0.49 kg
Item Weight	0.6 lbs
Length	5.2 inches
Width	1.43 inches
Height	2.42 inches
Material	Steel
Color	Black
Mountable	Din-Rail   Surface Mount   Wall Mount

## Specifications Cont.

### CONNECTIONS

USB Specification	USB 2.0
Maximum Data Rate	480 Mbps
Downstream Port Count	6
Downstream Port Type	6x Type A USB 2.0
Works as Standalone Charger	N - Requires Host to function
Can be Bus Powered	N - External Power Required

### Power

Input Voltage	7 ~ 48V DC
Power Connector	Phoenix 2-pin
Idle Power Draw	40mA @ 12 VDC
Max Power Draw	17.5W
Max Per Port Draw	1.5A (7.5W)

### ENVIRONMENTAL

Operating Temperature	0C ~ 60C
Storage Temperature	-20C ~ 75C
Operating Humidity	5% to 95% RH

### OS SUPPORT

Supported Operating Systems	Linux   Windows 10   Windows 8   Windows 7
-----------------------------	--

### WARRANTY

Warranty Period	1 Year
-----------------	--------

### PRODUCT URL

CG-6PU2MGD Product Page	<a href="https://www.coolgear.com/product/6-port-managed-usb-2-0-hub-w-15kv-esd-surge-protection">https://www.coolgear.com/product/6-port-managed-usb-2-0-hub-w-15kv-esd-surge-protection</a>
-------------------------	---