

Technical Data Sheet Rev 05.230616

ChargeIT! Mini Desktop 75W Dual Port USB-A & USB-C PD Charger w/ PPS & QC4.0 Support

Model Number: CG-CMD60W



Features

- Downstream: 1 USB Type-A QC Port, 1 USB Type-C PD Port
- Power Connector: 2-Pin Terminal Block
- Mounting Options: Wall, Surface, & Desktop
- LED Indicators: Power
- Supports USB PD4.0 including Programmable Power Supply

Package Contents

- Charger
- Mounting Bracket
- Power Cable
- Power Supply
- Screw Pack

| 50 | ecit | | ons |
|----|------|------|-----|
| Οp | 0011 | loui | |
| | | | |

OVERVIEW

| OVERVIEW | | |
|------------------------|--------------------------------------|--------------------------------------|
| Model No | CG-CMD60W | |
| Product Type | USB Charger | |
| Compliance | None or N/A | |
| UPC | 045079163461 | |
| Country of Origin | China | |
| LED indicators | Power | |
| Chipset | Cypress CCG3PA | |
| Electrical Protections | ±15kV (air), ±8kV (contact) | |
| PHYSICAL | | |
| Ship Weight (lbs) | 1.39 lbs | |
| Ship Weight (kg) | 0.63 kg | |
| Item Weight | 0.281 lbs | |
| Length | 2.38 inches | |
| Width | 1.97 inches | |
| Height | 1.03 inches | |
| Material | Steel | |
| Color | White | |
| Mountable | Desktop Surface Mount Wall Mount | Questions? Visit: coolgear.com/suppo |



| Specifications Cont. | | |
|--------------------------------------|---|--|
| CONNECTIONS | | |
| USB Specification | Charging Only | |
| Maximum Data Rate | N/A | |
| Downstream Port Count | 2 | |
| Downstream Port Type | 1x Type A (Charging) 1x Type C (Charging) | |
| Works as Standalone Charger | Y - Can be used without Host | |
| Can be Bus Powered | N - External Power Required | |
| Power | | |
| Input Voltage | 12 ~ 24V DC | |
| Min Input Voltage | 9V | |
| Max Input Voltage (DO NOT EXCEED) | 28V | |
| Power Connector | Phoenix 2-pin | |
| Idle Power Draw | 5mA @ 12V DC | |
| Max Power Draw | 75W | |
| Max Per Port Draw | 60W (Type-C) 15W (Type-A) | |
| Supported Charge Protocols | Apple Charge 2.4A DCP PD PPS QC 4.0 / 3.0 / 2.0 | |
| ENVIRONMENTAL | | |
| Operating Temperature | 0C ~ 55C | |
| Storage Temperature | -20C ~ 75C | |
| Operating Humidity | 5% to 95% RH | |
| OS SUPPORT | | |
| Supported Operating Systems | OS independent - No software or drivers required | |
| WARRANTY | | |
| Warranty Period | 1 Year | |
| PRODUCT URL | | |
| CG-CMD60W Product Page | https://www.coolgear.com/product/chargeit-mini-desktop-75w-dual-port-usb-a-usb-c-pd-charger-w-pps- qc4-0-support | |