

REV	LTR	DATE	REV. DIMENSION	DESIGN	APPROVE
A		2017.3.20	NEW DRAWING	Alvin	

  

1000 ± 30mm

Pin Assignment

Type C F (3)

Type C MALE (4)

### PIN ASSIGNMENT

(TYPE-C3.0) P2 (TYPE-C3.0)

A1	B1	A12	B12	-BLACK
电線 (Unit: 0.002)				
A4	B4	A9	B9	-RED
A5	A5 橙			
A6	A6 UTP-D- GREEN			
A7	A7 UTP-D- WHITE			
A2	A2 SUPP1-ORANGE			
A3	A3 SUPP1- PURPLE			
B11	B11 SUPP2- YELLOW			
B10	B10 SUPP2- BLUE			
B5	B5 棕			
SHELL ——— SHELL				

  

### ELECTRICAL PROPERTIES:

- Contact Resistance: 3 ohm MAX
- Insulation Resistance: 5Mega ohm MIN
- Hi-Pot: 300V DC/10ms

NO.	DESCRIPTION	Q'TY
④	TYPE C MALE (GOLD FALSH)	1
③	TYPE C FEMALE (GOLD FALSH)	1
②	PVC 45P COLOR:BLACK	1
①	(1P*30AWG+D+AL+MY)*2C+30AWG*1P+30AWG*2C+24AWG*2C) +AL+BD ADB OD:4.5mm PVC JACKET:BLACK USB 3.0	1

  

**MODEL #:** CG-USB3PX2C-3ft

**PAGE:** 1 / 1

**NOTES:**

**SCALE:** 1mm = 1mm

**TOLERANCE:** +/- 0.15 mm

**CONTACT:** support@coolgear.com

**DRAW:** Jesse Woodward

**DATE:** 8/10/23

**UNIT:** mm

**SITE:** coolgear.com