

**Technical Data Sheet Rev 06-251028** 

# 16 Port Managed USB 3.2 Gen 1 Hub w/ 15KV ESD Surge Protection

Model Number: CG-16PU3MGD











#### **Features**

- Port Management Software: Control each individual ports' status, turn bus power on/off, and even reset the entire hub through software.
- Upstream: 2 USB ports, Type B connectors, Screw-lock type
- Downstream: 16 USB ports, Type A connectors, Screw-lock type
- LED Indicators: 16 LEDs for each downstream port
- Super Fast Speeds: 5Gbps data transfer

### **Package Contents**

- 2-Pin Terminal Block
- DIN rail bracket
- Driver/Software Disk
- Hub
- Mounting Bracket
- Screw Pack
- USB Cable

#### Specifications

| OVERVIEW     |  |              |         |  |
|--------------|--|--------------|---------|--|
| Product Note | Note: The last USB port of this hub (Port 16) does NOT support USB 2.0 / 1.1 devices. It is used to communicate with managing utilities. However, it still supports USB 3.2 Gen 1 devices. |              |         |  |
| Model No     | CG-16PU3MGD  | Product Type | USB Hub |  |
|              |  |              |         |  |

 Compliance
 REACH | RoHS
 UPC
 045079163348

 Country of Origin
 Taiwan
 LED indicators
 Port Status | Power

 Chipset
 GL3523
 Electrical Protections
 ±15kV (air), ±8kV (contact)

#### **PHYSICAL**

| Ship Weight (lbs) | 4.13 lbs  | Ship Weight (kg) | 1.87 kg      |
|-------------------|---|------------------|--------------|
| Item Weight       | 2.43 lbs  | Length           | 12.15 inches |
| Width             | 5.12 inches   | Height           | 1.74 inches  |
| Material          | Steel   | Color            | Black        |
| Mountable         | Desktop   Din-Rail Mount   Rack<br>Mount   Surface Mount   Wall Mount |                  |              |



| Specifications Cont.        |  |  |  |
|-----------------------------|--|--|--|
| ONNECTIONS                  |  |  |  |
| USB Specification           | USB 3.2 Gen 1  |  |  |
| Upstream Port Type          | USB 3.2G1 / 3.0 Type-B Female  |  |  |
| Maximum Data Rate           | 5 Gbps   |  |  |
| Downstream Port Count       | 16   |  |  |
| Downstream Port Type        | 16x Type A USB 3.2 G1 / 3.0  |  |  |
| Works as Standalone Charger | N - Requires Host to function  |  |  |
| Can be Bus Powered          | N - External Power Required  |  |  |
| POWER                       |  |  |  |
| Input Voltage               | 12 ~ 24V DC  |  |  |
| Power Connector             | Phoenix 2-pin  |  |  |
| Idle Power Draw             | 35mA @ 20 VDC, 30mA @ 24 VDC   |  |  |
| Max Power Draw              | 120W   |  |  |
| Max Per Port Draw           | 1.5A (7.5W)  |  |  |
| ENVIRONMENTAL               |  |  |  |
| Operating Temperature       | 0C ~ 55C   |  |  |
| Storage Temperature         | perature -20C ~ 75C  |  |  |
| Operating Humidity          | ng Humidity 5% to 95% RH   |  |  |
| OS SUPPORT                  |  |  |  |
| Supported Operating Systems | Linux   OSX 10   Windows 11   Windows 10   |  |  |
| WARRANTY                    |  |  |  |
| Warranty Period             | 1 Year   |  |  |
| PRODUCT URL                 |  |  |  |
| Product Page                | https://www.coolgear.com/product/16-port-managed-usb-3-2-gen-1-hub-w-15kv-esd-surge-protection |  |  |

## **USB CHARGING & CONNECTIVITY EXPERTS**

# **We Speak Your Speak**



When you reach out to Coolgear support, you'll find yourself in the hands of a solution-oriented and knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

**Visit Support**