



**Technical Data Sheet Rev 06-250609** 

# **USB 3.2 Gen 1 Mini 7 Port Hub Component w/ ESD Surge Protection – PCBA**

Model Number: CG-2x3510S7-BOARD





#### **Features**

- Compliant with USB 3.2 Gen 1 Specification
- 1 control pipe and 1 interrupt pipe
- ESD protection per port: ±15 kV(Air), ±15 kV(Contact)

### **Package Contents**

• Hub - Board Only







#### Specifications

| PR | OD | UCT | <b>TERMS</b> |
|----|----|-----|--------------|
|    |    |     |              |

| Product Terms     | NOTICE: Coolgear strongly recommends purchasing one to two (1–2) units for initial evaluation. This product is intended for integration, evaluation, and testing purposes only, to assess its suitability and identify potential modifications for a specific use case. It is not designed for single-use scenarios. Before integrating this product into your project or placing a large-quantity order, please contact Coolgear to discuss your project requirements. For more details, refer to the Development Product Terms below. |
|-------------------|---|
| Product Terms URL | https://www.coolgear.com/wp-content/uploads/2023/10/Coolgear_DEV_Product_Terms.pdf  |

#### **OVERVIEW**

| Model No               | CG-2x3510S7-BOARD | Product Type      | USB Hub |
|------------------------|-------------------|-------------------|---------|
| UPC                    | 045079160873      | Country of Origin | China   |
| LED indicators         | Power             | Chipset           | GL3510  |
| Electrical Protections | N/A               |                   |         |

#### **PHYSICAL**

| Ship Weight (lbs) | 0.2 lbs     | Ship Weight (kg) | 0.09 kg     |
|-------------------|-------------|------------------|-------------|
| Length            | 4.25 inches | Width            | 1.65 inches |
| Height            | 0.70 inches |                  |             |



| Specifications Cont.        |  |  |  |  |
|-----------------------------|--|--|--|--|
| CONNECTIONS                 |  |  |  |  |
| USB Specification           | USB 3.2 Gen 1  |  |  |  |
| Upstream Port Type          | USB 3.2G1 / 3.0 Type-B Female  |  |  |  |
| Maximum Data Rate           | 5 Gbps   |  |  |  |
| Downstream Port Count       | 7  |  |  |  |
| Downstream Port Type        | 7x Type A USB 3.2 G1 / 3.0   |  |  |  |
| Works as Standalone Charger | N - Requires Host to function  |  |  |  |
| Can be Bus Powered          | Y - Supports Bus Power   |  |  |  |
| POWER                       |  |  |  |  |
| Input Voltage               | 5V DC  |  |  |  |
| Power Connector             | DC barrel, 2.5 ID x 5.5 OD, Center Pin Positive  |  |  |  |
| Idle Power Draw             | 70 mA @5v  |  |  |  |
| Max Power Draw              | 15W  |  |  |  |
| Max Per Port Draw           | 500 mA (2.5w)  |  |  |  |
| ENVIRONMENTAL               |  |  |  |  |
| Operating Temperature       | 0C ~ 55C   |  |  |  |
| Storage Temperature         | -20C ~ 75C   |  |  |  |
| Operating Humidity          | 5% to 95% RH   |  |  |  |
| OS SUPPORT                  |  |  |  |  |
| Supported Operating Systems | OS independent - No software or drivers required   |  |  |  |
| WARRANTY                    |  |  |  |  |
| Warranty Period             | 1 Year   |  |  |  |
| PRODUCT URL                 |  |  |  |  |
| Product Page                | https://www.coolgear.com/product/7-port-usb-3-2-gen-1-mini-powered-hub-w-esd-surge-protection-pcba |  |  |  |

## **USB CHARGING & CONNECTIVITY EXPERTS**

# **We Speak Your Speak**



When you reach out to Coolgear support, you'll find yourself in the hands of a solution-oriented and knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

