



Technical Data Sheet Rev 10-261008

7 Port USB 3.2 Gen 1 Hub PCBA w/ 15KV ESD Surge Protection & Port Status LEDs

Model Number: **CG-7PU31HB-PCBA**



Features

- Compact hub PCBA expands to 7 USB 3.1 ports
- Compliant with USB 3.2 Gen 1 Specifications
- 15KV ESD Surge Protection per port
- Supports 5Gbps (Super-speed), 480Mbps (High-speed), 12Mbps (Full-speed) and 1.5Mbps (Low-speed) Speed

Package Contents

- Hub - Board Only

OVERVIEW

SKU	CG-7PU31HB-PCBA
UPC	045079159648
Country of Origin	Taiwan
Manufacturer	CoolGear
Warranty	One Year
Certifications	REACH, RoHS, TAA
Product URL	https://www.coolgear.com/product/7-port-usb-3-2-gen-1-hub-pcba-w-15kv-esd-surge-protection-port-status-leds

PHYSICAL

Item Dimensions (Inches) (LxWxH)	6.03 × 2.34 × 1.05 in.
Package Weight (lbs)	0.14 lbs
Color	Yellow
Mounting Style	Bare PCB

TECHNICAL DATA

LED Indicators	Port Status, Power
----------------	--------------------

Chipset	GL3523
---------	--------

PACKAGE CONTENTS

CONNECTIONS

USB Specification	USB 3.2 Gen 1 (5Gbps)
-------------------	-----------------------

Downstream Port	7x Type A USB 3.2 Gen 1 (5Gbps)
-----------------	---------------------------------

Upstream Port	1x Type B USB 3.2 Gen 1 (5Gbps)
---------------	---------------------------------

Screw Lock Compatible	No
-----------------------	----

POWER

Works as Standalone Charger (Does Not Require Host)	Y - Can be used without Host
---	------------------------------

Power Input Connector Type	DC Barrel (5.5mm OD x 2.5mm ID, Center Pin Positive)
----------------------------	--

Input Voltage Range (V DC)	7 ~ 24V DC
----------------------------	------------

Maximum Per Port Draw	1.5A
-----------------------	------

Idle Power Draw	37.67mA Bus Powered, 68.2mA @ 12V Terminal Power
-----------------	--

Over Current Protection	Yes
-------------------------	-----

Over Voltage Protection	Yes, per buck
-------------------------	---------------

ESD Protection	15kV
----------------	------

Isolated	Yes
----------	-----

Charging Protocols	Apple Charge 2.4A, BC 1.2, CDP, DCP
--------------------	-------------------------------------

Charging Downstream Port (CDP) Support	Yes
--	-----

Dedicated Charging Port (DCP) Support	Yes
---------------------------------------	-----

ENVIRONMENTAL

Operating Temperature	0C ~ 55C
-----------------------	----------

Storage Temperature	-20C ~ 75C
---------------------	------------

Humidity	5% to 95% RH
----------	--------------

OS / SOFTWARE

OS Compatibility	<ul style="list-style-type: none"> • Windows 11 • Windows 10 • Windows 8 • Windows 7 • Linux • Mac OS • OS independent - No software or drivers required
------------------	---

USB CHARGING & CONNECTIVITY EXPERTS

We Speak Your Speak

When you reach out to Coolgear support, you'll find yourself in the hands of a solution-oriented and knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

[Visit Support](#)