

Technical Data Sheet Rev 06-241115

# USB-C to USB-A Power Delivery Adapter with Mounting Kit

Model Number: CG-UCUSBPD



## Features

- Compliant with USB 3.2 Gen1 and Gen2
- One upstream Type-C Connector Supports PD Capable Host
- Detachable Mounting Kit for Wall or DIN Rail Mounting Options
- Supports PD Profiles: 20V/5A, 14.5V/2A, 12V/3A and 5V/3A
- \* Notice: This product does NOT support USB-C DisplayPort (DP/Video Alt Mode) and is intended for data and power functionality only

## Package Contents

- Hub
- Mounting Bracket
- USB Cable

## Specifications

### OVERVIEW

|                        |              |
|------------------------|--------------|
| Model No               | CG-UCUSBPD   |
| Product Type           | USB Chargers |
| Compliance             | None or N/A  |
| UPC                    | 045079158894 |
| Country of Origin      | Taiwan       |
| LED indicators         | None or N/A  |
| Electrical Protections | N/A          |

### PHYSICAL

|                   |               |
|-------------------|---------------|
| Ship Weight (lbs) | 1.33 lbs      |
| Ship Weight (kg)  | 0.6 kg        |
| Length            | 3.24 inches   |
| Width             | 1.74 inches   |
| Height            | 0.87 inches   |
| Material          | Plastic       |
| Color             | Gray          |
| Mountable         | Surface Mount |

## Specifications Cont.

### CONNECTIONS

|                       |                               |
|-----------------------|-------------------------------|
| USB Specification     | USB 3.2 Gen 1                 |
| Upstream Port Type    | USB 3.2G1 / 3.0 Type-C Female |
| Maximum Data Rate     | 10 Gbps                       |
| Downstream Port Count | 1                             |
| Downstream Port Type  | 1x Type A USB 3.2 G2          |

### POWER

|                            |             |
|----------------------------|-------------|
| Input Voltage              | 19 ~ 20V DC |
| Supported Charge Protocols | PD          |

### ENVIRONMENTAL

|                       |              |
|-----------------------|--------------|
| Operating Temperature | 0C ~ 55C     |
| Storage Temperature   | -20C ~ 75C   |
| Operating Humidity    | 5% to 95% RH |

### OS SUPPORT

|                             |  |
|-----------------------------|--|
| Supported Operating Systems | OS independent - No software or drivers required |
|-----------------------------|--|

### WARRANTY

|                 |        |
|-----------------|--------|
| Warranty Period | 1 Year |
|-----------------|--------|

### PRODUCT URL

|              |   |
|--------------|---|
| Product Page | <a href="https://www.coolgear.com/product/usb-c-to-usb-a-power-delivery-adapter-mounting-kit">https://www.coolgear.com/product/usb-c-to-usb-a-power-delivery-adapter-mounting-kit</a> |
|--------------|---|

## USB CHARGING & CONNECTIVITY EXPERTS

# We Speak Your Speak



When you reach out to Coolgear support, you'll find yourself in the hands of a solution-oriented and knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

[Visit Support](#)