


Coolgear, Inc. 5120 110th Ave N Clearwater, FL 33760 USA **P:** +1-727-209-1300 **F:** +1-727-209-1302 **coolgear.com**

Technical Data Sheet Rev 06-250609

USB PD Integrator Board for 150W Charging USB C/A Multi-Port – PCBA

Model Number: CGL-4P150BRD



Features

- 4x Downstream USB Type-C Power Delivery ports supporting up to 41.4W per port
- 4x Downstream USB Type-A Legacy Port with QC 3.0/Apple Fast Charge supporting up to 18W per port
- Supports USB-PD Power Delivery Profiles: 5V/2.39A, 9V/2.39A, 12V/2.31A
- Backwards compatible with all USB standards BC 1.2 and Apple Fast Charge as well as QC3.0
- Works with ALL USB-PD Device as well as Legacy Type-A devices

Package Contents

• Hub - Board Only

Specifications				
PRODUCT TERMS				
Product Terms	This product is intended for suitability and identify pote single-use scenarios. Befor order, please contact Cool	NOTICE: Coolgear strongly recommends purchasing one to two (1–2) units for initial evaluation. This product is intended for integration, evaluation, and testing purposes only, to assess its suitability and identify potential modifications for a specific use case. It is not designed for single-use scenarios. Before integrating this product into your project or placing a large-quantity order, please contact Coolgear to discuss your project requirements. For more details, refer to the Development Product Terms below.		
Product Terms URL	https://www.coolgear.com/	https://www.coolgear.com/wp-content/uploads/2023/10/Coolgear_DEV_Product_Terms.pdf		
OVERVIEW				
Model No	CGL-4P150BRD	Product Type	USB Chargers	
UPC	045079161061	Country of Origin	China	
LED indicators	None or N/A	Electrical Protections	4KV	
PHYSICAL	·	nn		
Ship Weight (Ibs)	0.19 lbs	Ship Weight (kg)	0.09 kg	
Item Weight	0.19 lbs	Length	6.85 inches	
Width	2.43 inches	Height	0.69 inches	



Specifications Cont.			
CONNECTIONS			
Maximum Data Rate	N/A		
Downstream Port Count	8		
Downstream Port Type	4x Type A (Charging) 4x Type C (Charging)		
POWER			
Input Voltage	24V DC		
Supported Charge Protocols	Apple Charge 2.4A BC 1.2 DCP PD QC 3.0 / 2.0		
ENVIRONMENTAL			
Operating Temperature	0C ~ 55C		
Storage Temperature	-20C ~ 75C		
Operating Humidity	5% to 95% RH		
OS SUPPORT			
Supported Operating Systems	OS independent - No software or drivers required		
WARRANTY			
Warranty Period	1 Year		
PRODUCT URL			
Product Page	https://www.coolgear.com/product/usb-pd-integrator-board-for-130w-charging-usb-c-a-multi- port-board-12vpdo		

USB CHARGING & CONNECTIVITY EXPERTS



We Speak Your Speak

When you reach out to Coolgear support, you'll find yourself in the hands of a solution-oriented and knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

