

Technical Data Sheet Rev 06-250801

RS232 Serial to RS422/485 w/2000V DC Optical Isolation and Surge

Model Number: **SER-COMi-Si-M**



Features

- Industrial Quality Optical Isolated RS-232 to RS-422/485 Converter
- RS232: DTE/DCE selected by DIP
- RS485 BIAS: BIAS (polarization) optical isolated by special drivers, controlled via software configuration
- Operation Modes: RS422 RS485 by RTS RS485 by DTR RS485 by ART (Automatic Receive Transmit control)
- Power Requirements: 9-28V DC, 600mW. Power Supply Adapter: 12V DC, 500mA

Package Contents

- Adapter
- DB9 to DB9 Cable
- Power Cable

Specifications

OVERVIEW

Model No	SER-COMi-Si-M	Product Type	USB Serial Adapter
Compliance	CE FCC	UPC	045079160880
Country of Origin	Taiwan	LED indicators	Port Status TX/RX
Electrical Protections	25kv		

PHYSICAL

Ship Weight (lbs)	0.94 lbs	Ship Weight (kg)	0.43 kg
Item Weight	0.22 lbs	Length	6.375 inches
Width	4.75 inches	Height	2.125 inches
Material	Steel	Color	Black
Mountable	Din-Rail Mount Surface Mount Wall Mount	Cable Length (in)	10
Cable Length (m)	0.25		

Specifications Cont.**CONNECTIONS**

Connector(s)	3-Pin Terminal Block 5-pin Terminal Block DB9 Female w/ Nuts DB9 Male w/ Nuts
---------------------	---

SERIAL SPECS

Maximum Data Rate	1Mbps
Minimum Data Rate	300 baud/bps
Serial Modes	RS232 RS422 RS485
RS422 Signals	TxD-, TxD+, RxD+, RxD-, GND, RTS-, RTS+, CTS+, CTS-
RS485 2-wire Signals	DATA-, DATA+, GND
RS485 4-wire Signals	TxD-, TxD+, RxD+, RxD-, GND

ENVIRONMENTAL

Operating Temperature	0C ~ 60C
Storage Temperature	-20C ~ 85C
Operating Humidity	5% to 95% RH

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8 Windows 7 Windows Vista Windows XP
------------------------------------	---

WARRANTY

Warranty Period	1 Year
------------------------	--------

PRODUCT URL

Product Page	https://www.usbgear.com/ser-comi-si-m.html
---------------------	---