

Technical Data Sheet Rev 06-250807

Internal Bay USB 3.0 4-Port VIA USB 3.0 SuperSpeed Chip Hub with LED

Model Number: USB3-1X4INT









Features

- 4-Port USB 3.0 VIA Chip Super-Speed USB 3.0 Internal 3.5 inch Bay Mount Hub
- 4 Downstream Ports (Type-A) Support Super-Speed, High-speed, Full-speed and Low-speed Traffic
- Supports Self-powered and Bus-powered Mode
- Built-in Single Chip USB 3.0 Hub Controller
- Supports 4 Concurrent Non-periodic Transactions

Package Contents

- Hub
- Mounting Bracket
- Power Cable
- USB Cable

Specifications

| OV | ER | VI | E١ | N |
|----|-----------|----|----|---|
|----|-----------|----|----|---|

| Model No | USB3-1X4INT | Product Type | USB Hub |
|-------------------|-------------|------------------------|--------------|
| Compliance | None or N/A | UPC | 729440625214 |
| Country of Origin | Taiwan | LED indicators | Port Status |
| Chipset | VL817 | Electrical Protections | N/A |

PHYSICAL

| Ship Weight (lbs) | 0.32 lbs | Ship Weight (kg) | 0.15 kg |
|-------------------|-------------|------------------|-------------|
| Item Weight | 0.13 lbs | Length | 3.98 inches |
| Width | 3.54 inches | Height | 0.98 inches |
| Material | Plastic | Color | Black |
| Mountable | N/A | | |





Specifications Cont.

| CONNECTIONS | | |
|-----------------------------|---|--|
| USB Specification | USB 3.2 Gen 1 | |
| Upstream Port Type | USB 3.2G1 / 3.0 Type-B Female | |
| Maximum Data Rate | 5Gbps | |
| Downstream Port Count | 4 | |
| Downstream Port Type | 4x Type A USB 3.2 G1 / 3.0 | |
| Works as Standalone Charger | N - Requires Host to function | |
| Can be Bus Powered | Y - Supports Bus Power | |
| POWER | | |
| Input Voltage | 5V DC | |
| Power Connector | 4-Pin Molex | |
| Max Per Port Draw | 900mA | |
| OS SUPPORT | | |
| Supported Operating Systems | Linux OSX 10 Windows 7 Windows Vista Windows XP | |
| WARRANTY | | |
| Warranty Period | 1 Year | |
| PRODUCT URL | | |
| Product Page | https://www.usbgear.com/usb3-1x4int.html | |