



PIN OUT	
P1	P2
1	RED
2	WHITE
3	GREEN
4	BLACK
5	BLUE
6	YELLOW
7	DRAIN
8	PURPLE
9	ORANGE
SHELL	DRAIN+BRAID
SHELL	SHELL

NOTE:

1. 100% OPEN & SHORT WIRE TEST;
2. CONTACT RESISTANCE 2ohm Max;
3. INSULATION RESISTANCE 10M ohm Min;
4. HI-POT DC 300V/0.01S;

NO.	MATERIAL. P/N	DESCRIPTION	Q' TY	VENDOR
7	SCREW	Black NICKEL-CU #4-40UNC (Low Lead-CU Below 1000ppm)	2PCS	
6	OUT-MOLD	PVC 45P BLACK	14G	
5	IN-MOLD	PE	6G	
4	COPPER	COPPER FOIL T:0.65*W:8*L:20MM	2PCS	
3	CONN 2	USB (3.0) B TYPE MALE BLUE PIN/GF NICKEL-SHELL	1SET	
2	CONN 1	USB (3.0) A TYPE MALE BLUE PIN/GF NICKEL-SHELL	1SET	
1	CABLE	UL20276 (USB3.0 Cable) (1P#28+DAM)*2C+1P#28+20#24+AL+D+B(16/6/0.12AL) OD:5.5MM BLACK PVC L:xxxxMM	1PCS	

CABLEMAX	MODEL #:	USB3-SLBA
	PAGE:	1 / 1
DRAW:	Jesse Woodward	USB 3.2 Gen 1 Type-B Screw-Lock to Type-A Cable
	DATE:	
UNIT:	01/15/2026	mm
	SCALE:	
SITE:	coolgear.com	CONTACT: support@gearmo.com