Coolgear, Inc.
5120 110th Ave N
Clearwater, FL 33760 USA

P: +1-727-209-1300
F: +1-727-209-1302
coolgear.com

Technical Data Sheet Rev 06-250801

7 Port USB 3.2 Gen 1 Hub w/ Surge Protection & Screw-Locking Ports

Model Number: **USBG-7U3ML**

Features

- USB 3.2 Gen 1 ports deliver speeds up to 5Gbps, enabling seamless high-speed communication
- Screw-lock compatible ports to prevent accidental disconnections
- Rugged metal housing withstands harsh environments, ideal for many industrial uses including ATM's, Kiosks, Warehouses, Data Centers, and more
- Supports surface, wall, and DIN-Rail mounting for easy integration into various setups - includes 6 foot USB A to B cable.
- NOTE: Power Supply not included. Available as an optional part Model # USBG-7U3ML-PS

Package Contents

- 2-Pin Terminal Block
- DIN rail bracket
- Hub
- Screw Lock USB Cable
- Screw Pack
- User Manual

Specifications

OVERVIEW

Model No	USBG-7U3ML	**Product Type**	USB Hub
Compliance	REACH | RoHS | TAA	**UPC**	729440691479
Country of Origin	Taiwan	**LED indicators**	Power
Chipset	GL3523	**Electrical Protections**	±15kV (air), ±8kV (contact)

PHYSICAL

Ship Weight (lbs)	2 lbs	**Ship Weight (kg)**	0.91 kg
Item Weight	0.775 lbs	**Length**	5.66 inches
Width	2.6 inches	**Height**	1.42 inches
Material	Steel	**Color**	Black
Mountable	Din-Rail Mount | Surface Mount | Wall Mount		

Coolgear, Inc.
5120 110th Ave N
Clearwater, FL 33760 USA

P: +1-727-209-1300
F: +1-727-209-1302
coolgear.com

Specifications Cont.

CONNECTIONS	
USB Specification	USB 3.2 Gen 1
Upstream Port Type	USB 3.2G1 / 3.0 Type-B Female
Maximum Data Rate	5 Gbps
Downstream Port Count	7
Downstream Port Type	7x Type A USB 3.2 G1 / 3.0
Works as Standalone Charger	Y - Can be used without Host
Can be Bus Powered	Y - Supports Bus Power
Bus Power Isolation	Y
POWER	
Input Voltage	7 ~ 24V DC
Min Input Voltage	7V
Max Input Voltage	24V
Power Connector	Phoenix 2-pin
Idle Power Draw	37.9 mA Bus Powered 70 mA @ 12V Terminal Power
Max Power Draw	50W
Max Per Port Draw	1.5A (7.5W)
Supported Charge Protocols	Apple Charge 2.4A	DCP
ENVIRONMENTAL	
Operating Temperature	0C ~ 55C
Storage Temperature	-20C ~ 75C
Operating Humidity	5% to 95% RH
OS SUPPORT	
Supported Operating Systems	Linux	OSX 10	Windows 11	Windows 10	Windows 8	Windows 7
WARRANTY	
Warranty Period	1 Year
PRODUCT URL	
Product Page	https://www.coolgear.com/product/7-port-usb-3-hub-with-din-rail-mount

When you reach out to Coolgear support, you'll find yourself in the hands of a solution-oriented and knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

Visit Support