

**Technical Data Sheet Rev 06-250807** 

## **USB Isolator 3000 Vrms Rugged Metal Chassis**

Model Number: USBG-ISO-M



#### **Features**

- Rugged, industrial-grade full / low speed USB isolator that provides high-voltage 3kV isolation to protect the host computer and valuable USB industrial and medical equipment.
- Provides electrical isolation up to 3000 Vrms upstream to downstream USB port.
- Features 5V isolated pass-thru power up to 420 mA to downstream device.
- Supports USB 2.0 full speed 12 Mbps by default setting - USB1.1 low speed 1.5 Mbps data rate selectable by jumpers.
- Supports bus power, no software or drivers installation required. Includes integrated USB cable.

#### **Package Contents**

- Adapter
- DIN rail bracket
- USB Cable

| Specifications    |                               |                        |              |  |
|-------------------|-------------------------------|------------------------|--------------|--|
| OVERVIEW          |                               |                        |              |  |
| Model No          | USBG-ISO-M                    | Product Type           | USB Isolator |  |
| Compliance        | CE   FCC   REACH   RoHS   TAA | UPC                    | 729440692216 |  |
| Country of Origin | Taiwan                        | LED indicators         | Power        |  |
| Chipset           | ADUM4168                      | Electrical Protections | 15kV         |  |
| PHYSICAL          |                               |                        |              |  |
| Ship Weight (lbs) | 0.6 lbs                       | Ship Weight (kg)       | 0.27 kg      |  |
| Item Weight       | 0.42 lbs                      | Length                 | 2.87 inches  |  |

| Ship Weight (lbs) | 0.6 lbs                                     | Ship Weight (kg)  | 0.27 kg     |
|-------------------|---|-------------------|-------------|
| Item Weight       | 0.42 lbs                                    | Length            | 2.87 inches |
| Width             | 2.04 inches                                 | Height            | 0.98 inches |
| Material          | Steel                                       | Color             | Black       |
| Mountable         | Din-Rail Mount   Surface Mount   Wall Mount | Cable Length (ft) | 3           |
| Cable Length (in) | 36  | Cable Length (m)  | 0.91        |



| Specifications Cont.        |   |  |
|-----------------------------|---|--|
| CONNECTIONS                 |   |  |
| USB Specification           | USB 2.0   |  |
| Downstream Port Count       | 1   |  |
| Downstream Port Type        | Type-A  |  |
| Can be Bus Powered          | Y - Supports Bus Power  |  |
| ENVIRONMENTAL               |   |  |
| Operating Temperature       | -40C ~ 70C  |  |
| Storage Temperature         | -40C ~ 85C  |  |
| Operating Humidity          | 5% to 95% RH  |  |
| OS SUPPORT                  |   |  |
| Supported Operating Systems | Linux   OSX 10   Windows 11   Windows 10   Windows 8   Windows 7   Windows Vista   Windows XP |  |
| WARRANTY                    |   |  |
| Warranty Period             | 1 Year  |  |
| PRODUCT URL                 |   |  |
| Product Page                | https://www.coolgear.com/product/usb-isolator-3000-vrms-rugged-metal-chassis                  |  |

### **USB CHARGING & CONNECTIVITY EXPERTS**

# **We Speak Your Speak**



When you reach out to Coolgear support, you'll find yourself in the hands of a solution-oriented and knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

**Visit Support**